

Application No.: 09/651,915 • Filed: August 31, 2000

Group Art Unit: 2771

On page 69, line 25, following "control and data over Ethernet", please delete "32" and insert therefor - - 41 - -.

In the Drawings

Please amend Figures 9b, 16c, 17, 18, 19, 20, 23, 26, 35, and 55 as shown in red in the attached drawings.

REMARKS

Applicants respectfully request that the Examiner enter the amendments set forth above prior to examining the above-referenced application.

Applicant amend the specification and Figures 9b, 16c, 17, 18, 19, 20, 23, 26, 35, and 55 to correct typographical errors. Specifically, reference numeral 32 is a duplicate. Therefore Applicants replace reference numeral 32 with reference numeral 41 in both the specification and Figures 9b, 16c, 17, 18, 19, 20, 23, and 26. Applicants add reference numeral 41 to the connection between NMS 60 and the network device 540 in Figure 35. Reference numeral 838 is added to the input marked "Alt. Input from other EX CTS" in Figure 55. Both reference numeral 41 and reference numeral 838 are referred to in the specification and used in other figures to designate the same part of the invention. No new matter is added by these amendments.

In addition, Applicants amend Figure 55 to remove an extraneous line section to indicate the correct connection of the *output* 770 to the Alt. *output* to other EX CTS. Support for this amendment can be found throughout the specification, for example, on page 192, lines 29-31, and page 193, line 1. In particular, the specification recites that "the output 770 (marked "Alt. Output to other EX CTS") of timing module 76 may be provided to the other



Application No.: 09/651,915 Filed: August 31, 2000 Group Art Unit: 2771

EX CTS and received as input 838 (marked "Alt. Input from other EX CTS"). Thus, no new matter is added by this amendment.

For the Examiner's convenience, Applicants enclose a copy of page 69 of the specification in which the above corrections are indicated in red.

The Examiner is urged to telephone the undersigned Attorney for Applicant in the event that such communication is deemed to expedite prosecution of this matter.

Respectfully submitted,

Date: 12/14/00

Lisa J. Michaud Reg. No. 44,238

Attorney for Applicant(s)

Nutter, McClennen & Fish, LLP One International Place Boston, MA 02110-2699

Tel: (617)439-2550 Fax: (617)310-9550

934819.1

infiguration database and NMS database are downloaded and upgraded (as described below) without re-booting the computer system.

Network Management System (NMS):


Referring to Fig. 9a, as described above, a user / network administrator of computer system 10 works with network management system (NMS) software 60 to configure computer system 10. In the embodiment described below, NMS 60 runs on a personal computer or workstation 62 and communicates with central processor 12 over Ethernet network (out-of-band). Instead, the NMS may communicate with central processor 12 over data path 34 (Fig. 1, in-band). Alternatively (or in addition as a back-up communication port), a user may communicate with computer system 10 through a console interface / terminal (840, Fig. 2a) connected to a serial line 66 connecting to the data or control path using a command line interface (CLI) protocol. Instead, NMS 60 could run directly on computer system 10 provided computer system 10 has an input mechanism for the user.


During installation, an NMS database 61 is established on, for example, work-station 62 using a DDL executable file corresponding to the NMS database. The DDL file may be downloaded from persistent storage 21 in computer system 10 or supplied separately with other NMS programs as part of an NMS installation kit. The NMS database mirrors the configuration database through an active query feature (described below). In one embodiment, the NMS database is an Oracle database from Oracle Corporation in Boston, Massachusetts.


The NMS and central processor 12 pass control and data over Ethernet using, for example, the Java Database Connectivity (JDBC) protocol. Use of the JDBC protocol allows the NMS to communicate with the configuration database in the same manner that it communicates with its own internal storage mechanisms, including the NMS database. Changes made to the configuration database are passed to the NMS database to ensure that both databases store the same data. This synchronization process is much more efficient, less error-prone and timely than older methods that require the NMS to

898375 68














Ł














This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:		
☐ BLACK BORDERS		
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES		
FADED TEXT OR DRAWING		
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING		
☐ SKEWED/SLANTED IMAGES		
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS		
☐ GRAY SCALE DOCUMENTS		
☐ LINES OR MARKS ON ORIGINAL DOCUMENT		
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY		

IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.



Creation date: 09-21-2004

Indexing Officer: DSANFORD - DEBRA SANFORD

Team: OIPEBackFileIndexing

Dossier: 09653700

Legal Date: 12-20-2000

No.	Doccode	Number of pages
1	A	1
2	REM	15

Total number of pages: 16

Remarks:

Order of re-scan issued on